Storage Vaults

- Designed to comply with the Flammable Liquid Storage Regulations (1972) as appropriate & the Factory Inspection Guide HSG51
- Adjustable vent meets the requirements of both Flammable Storage (vents closed) & Agrochemicals (vents open)
- All welded units conforming to the A.P. E.A. construction requirements
- Provide a half hour protection from collapse & the passage of flame
- Multi-lockable for high security & fitted with a lift up action lid assisted by gas struts
- For extra protection & fork lifting the units have skids on the base
- Middle shelves pivot on models SSV01Z & SSV02Z to enable larger items to be stored at base level
- Model SSV03Z has a central partition & four shelves - the two middle shelves fold away & the two top shelves are made in 3 sections - the back section is fixed in position & the front two sections removable
- All models have a liquid-tight base to contain spillage

N.B. A fork lift will be needed to unload these vaults



SAFETY NOTE

Before storage of herbicides & petroleum based products takes place the advice of the following should be sought for specific guidance

- Health & Safety Inspector
- Trading Standards Officers
- Environmental Health Officers
- Fire Officers









Storage Vaults					
Size W.D.H.	Liquid tight sealed base unit capacity	Shelves	Weight	Code	Price
700.850.1270	120 Litres	2 Shelves 690 x 400 fixed (top) & 690 x 400 pivots (middle)	180 kg	SSV01Z	£1,366.50
1370.850.1270	250 Litres	2 Shelves 1360 x 400 fixed (top) & 1360 x 400 pivots (middle)	260 kg	SSV02Z	£1,924.05
2500.1080.1270	550 Litres	4 Shelves 1220 x 500 fixed	460 kg	SSV03Z	£3,435.55